



SHOWN WITH BUILT-IN FRONT PANEL CONTROLS  
 (INCLUDED ONLY ON MULTI-FUNCTION  
 CLOCK/TIMER VERSIONS)

6FT. POWER MODULE INCLUDED  
 12VAC, 1 AMP (0900-7025)

**SPECIFICATIONS**

AE26R-427A GPS MASTER CLOCK  
 BLACK ANODIZED ALUMINUM ENCLOSURE (19"W X 3.5"H X6"D)  
 FITS STANDARD 19" RACK  
 VISIBLE UP TO 100 FEET AWAY  
 OPERATES FROM 12 VAC, 1 A. MAX, 6 FT POWER MODULE PROVIDED  
 FIELD WIRING- TERMINAL BLOCKS)  
 1/8" RED ACRYLIC LENS  
 INPUT = GPS INPUT (3 WIRE) FROM GPS ANTENNA/RECEIVER  
 (PN: GPS-427A)  
 OUTPUT = RS232 SERIAL DATA (2 WIRE)  
 ADDRESS 15 = TIME OF DAY (12 OR 24 HOUR FORMAT)  
 ADDRESS 13 = DATE (MM DD YY)  
 ADDRESS 12 = DAY OF THE WEEK (1 THROUGH 7),  
 JULIAN DAY (001 THROUGH 365, 366 ON LEAP YEAR)

APPROVALS	DATE
DRAWN BY GJB	9/5/01
CHECKED BY	
APPROVED BY	

VCAD LTV\ATS DWG\VAE\AE2X\  
  
 P.D. BOX 5705  
 SHREVEPORT, LA  
 71135

PRODUCT	SCALE 1:4
AE26R-427A	JOB #
RACK MOUNT GPS MASTER CLOCK (LOW VOLTAGE)	SHEET #
DESCRIPTION	REVISION
FINISHED GOOD	FILENAME: AE26R-427A-LV DRAWING #