



SHOWN WITH BUILT-IN FRONT PANEL CONTROLS
(INCLUDED ONLY ON MULTI-FUNCTION
CLOCK/TIMER VERSIONS)

SPECIFICATIONS

AE26R-427A GPS MASTER CLOCK
BLACK ANODIZED ALUMINUM ENCLOSURE (19"W X 3.5"H X6"D)
FITS STANDARD 19" RACK
VISIBLE UP TO 100 FEET AWAY
OPERATES FROM 120 VAC, 100 MA. MAX, 8 FT POWER CORD PROVIDED
FIELD WIRING- TERMINAL BLOCKS)
3/8" RED ACRYLIC LENS
INPUT = GPS INPUT (3 WIRE) FROM GPS ANTENNA/RECEIVER
(PN: GPS-427A)
OUTPUT = RS232 SERIAL DATA (2 WIRE)
ADDRESS 15 = TIME OF DAY (12 OR 24 HOUR FORMAT)
ADDRESS 13 = DATE (MM DD YY)
ADDRESS 12 = DAY OF THE WEEK (1 THROUGH 7),
JULIAN DAY (001 THROUGH 365, 366 ON LEAP YEAR)

APPROVALS	DATE
DRAWN BY DTI	5-31-01
CHECKED BY	
APPROVED BY	

VCAD LTV\ATS DWG\AE\AE2X\ ATS APPLIED TECHNICAL SYSTEMS		P.D. BOX 5705 SHREVEPORT, LA 71135	
PRODUCT	AE26R-427A	SCALE	1:4
RACK MOUNT GPS MASTER CLOCK		JOB #	
DESCRIPTION		SHEET #	
FINISHED GOOD		REVISION	
		FILENAME	AE26R-427A
		DRAWING #	