



SPECIFICATIONS:

ENCLOSURE: (BOX .062 STEEL, FRONT PANEL .040 STEEL) BLACK POLANE TEXTURE
 0.5"X2.5" LCD DISPLAY
 OPERATES FROM EITHER 120VAC 60HZ OR 12VDC KEYHOLE MOUNTING ON BACK PANEL
 ONE SPDT RELAY RATED AT 15A RESISTIVE AT 120VAC OR 28VDC
 AUTO PROMPTING FEATURE GUIDES USER THROUGH SETUP PROCESS
 UP TO 30 PROGRAM STEPS AND UP TO 10 SKIP PLANS PROGRAMMABLE DAYLIGHT SAVINGS TIME ADJUSTMENT
 AUTOMATIC LEAP YEAR COMPENSATION
 OUTPUT RELAY MAY BE MANUALLY ENERGIZED AND DE-ENERGIZED
 OUTPUT MAY BE PULSED FROM 1 TO 99 SECONDS

APPROVALS	DATE
DRAWN BY DTI	8-7-01
CHECKED BY	
APPROVED BY	

VCAD LTVATS DWG\VP MC\21\

PROJECT

P.O. BOX 5705
 SHREVEPORT, LA
 71135

DESCRIPTION	SCALE
FINISHED GOOD	1:2
JOB #	
SHEET #	
REVISION	
FILENAME: AP21.FGI	
DRAWING #	